



1	DCD
2	RXD
3	TXD
4	DTR
5	GND
6	DSR
7	RTS
8	CTS
9	RI

DB9/F	RJ45
8	1 CTS
6	2 DSR
2	3 RXD
5	4 GND
5	5 GND
3	6 TXD
4	7 DTR
7	8 RTS



电气特性:
 1.100%开路、短路、断路测试。
 2.绝缘阻抗: 10M Ohm Min
 3.导通阻抗: 2 Ohm MAX
 4.耐压: DC 300V,0.01/Sec

NO.	PART NAME	SPEC DESCRIPTION	QT'Y	UNIT	CUSTOMER P/N:	P/N:ADB140010001
6	螺杆	镀镍, $\phi 2.3 \times 37 \text{mm}$	2	PCS	A INITIAL RELEASE 25/08/26 REV DESCRIPTION OF CHANGE DATE TOLERANCE INCHES MM .X .015 .30 .XX .010 .10 .XXX .005 .05 DRAWN BY TONY CHAN CHECK BY CUSTOMER P/N:	OIKWAN® 东莞市嵩群实业有限公司 DONGGUAN AIQUN INDUSTRIAL CO.,LTD. SCALE NONE UNIT MM SHEET 1/1 DATE 25/08/26 TITLE: DB9母-RJ45 REV A CUSTOMER: DWG NO:
5	插头	DB9母头, 插头镀镍, 蓝色胶芯	1	PCS		
4	胶料	LDPE	A/R	g		
3	胶料	45P PVC, 蓝色	A/R	g		
2	水晶头	RJ45 MALE, 8P8C, PIN G/F	1	PCS		
1	线材	28AWG*8C, BARE COPPER, 蓝色 PVC, ROHS	A/R	mm		