



RJ45 8P8C Pinout

P1	P2
PIN1	1 CTS
PIN2	2 DSR
PIN3	3 RXD
PIN4	4 GND
PIN5	5 GND
PIN6	6 TXD
PIN7	7 DTR
PIN8	8 RTS

电气特性:

- 1.100%开路、短路、断路测试。
- 2.绝缘阻抗: 10M Ohm Min
- 3.导通阻抗: 2 Ohm MAX
- 4.耐压: DC 300V,0.01/Sec

NO.	NAME	Description	QTY	Unit
6	胶料	45P PVC, 蓝色, MOLDED, ROHS	A/R	G
5	胶料	LDPE, MOLDED, ROHS	A/R	G
4	插头	USB C 公头 镀镍, ROHS	1	PCS
3	PCB	PCBA WITH FT232+ZT213 CHIP, ROHS	1	PCS
2	水晶头	RJ45 MALE, 8P8C, PIN G/F	1	PCS
1	线材	28AWG*8C, BARE COPPER, 蓝色 PVC JACKET, ROHS	A/R	M

A	INITIAL RELEASE		25/08/07					
REV	DESCRIPTION OF CHANGE		DATE					
TOLERANCE		东莞市嵩群实业有限公司 DONGGGUAN AIQUN INDUSTRIAL CO., LTD.						
INCHES					M/M			
.X	.015				.30			
.XX	.010				.10			
.XXX	.005	.05		SCALE	NONE		REV	A
DRAWN BY		TONY CHAN		UNIT	MM			
CHECK BY				SHEET	1/1	COSTOMER:		
CUSTOMER. P/N:				DATE	25/08/07	DWG NO.:		
				TITLE: USB C TO RJ45				
				P/N: ARJ110010001				