



受控文件②
2026-03-02
DIKWAN

WIRING TABLE

| CN1 | | CN2 | |
|-----|------------|-----|--------|
| KEY | WIRING | KEY | WIRING |
| 1 | DRAIN WIRE | 1 | |
| 2 | | 2 | |
| 3 | | 3 | |
| 4 | DRAIN WIRE | 4 | |
| 5 | | 5 | |
| 6 | | 6 | |
| 7 | DRAIN WIRE | 7 | |

电气特性:

1. 100%开路、短路、断路测试。
2. 绝缘阻抗: 10M Ohm Min
3. 导通阻抗: 2 Ohm MAX
4. 耐压: DC 300V, 0.01/Sec

| | | |
|-----|-----------------------|----------|
| A | INITIAL RELEASE | 26/02/26 |
| REV | DESCRIPTION OF CHANGE | DATE |

| TOLERANCE | | | DIKWAN® 东莞市谦群实业有限公司 DONGGUAN AIQUN INDUSTRIAL CO.,LTD | | | |
|-----------|--------|-----|---|--|--|--|
| | INCHES | MM | | | | |
| . X | .015 | .30 | | | | |
| . XX | .010 | .10 | | | | |
| . XXX | .005 | .05 | | | | |

| NO. | PART NAME | SPEC DESCRIPTION | QT'Y | UNIT | CUSTOMER P/N: | P/N: 1. AMSSS0010014 |
|-----|-----------|--|------|------|---------------|----------------------|
| 4 | 弹片 | 不锈钢弹片 | 2 | PCS | DRAWN BY | SCALE NONE |
| 3 | 胶料 | 45P PVC 黑色 ROHS | A/R | G | CHECK BY | UNIT MM |
| 2 | 插头 | SATA 7P插头, 端子镀金: G/F, 黑色橡胶芯, 弹片型 | 2 | PCS | APPD BY | SHEET 1/1 |
| 1 | 线材 | (30AWG*2C+2d)*AL+MYLAR, OD:0.97*2.17MM, 100±5 ohm. | A/R | mm | CUSTOMER P/N: | DATE 26/02/26 |
| | | | | | | REV A0 |
| | | | | | | CUSTOMER: |
| | | | | | | DWG NO: |
| | | | | | | TITLE: SATA-SATA |
| | | | | | | P/N: 1. AMSSS0010014 |