



电气特性:
 1. 100%开路、短路、断路测试。
 2. 绝缘阻抗: 10M Ohm Min
 3. 导通阻抗: 2 Ohm MAX
 4. 耐压: DC 300V, 0.01/Sec

NO.	NAME	MATERIAL DESCRIPTION	O' TY	UNIT	A	REV	DESCRIPTION OF CHANGE	DATE
5	防尘帽	8088防尘帽	2	PCS				25/12/01
4	胶料	本色低密度PE料	A/R	G				
3	装配件	锌合金组装壳 上盖+下盖 配卡钩 拉环 螺丝 硅胶圈	2	PCS				
2	PCB	MINI SAS 26P PCB板, PIN: Au 15U", 100±10ohm	2	PCS				
1	线材	(28AWG*2C+D+HMAM+HM)*8C+M+AM+B, OD: 7.5±0.15MM, BLACK PVC JACKET	A/R	mm				
					TOLERANCE		OIKWAN 东莞市嵩群实业有限公司 DONGGUAN AIQUN INDUSTRIAL CO.,LTD	
					INCHES		SCALE NONE	
					MM		UNIT MM	
					.X .015 .30		SHEET 1/1	
					.XX .010 .10		CUSTOMER:	
					.XXX .005 .05		DATE 24/7/30	
					DRAWN BY WSY		DWG NO:	
					CHECK BY		TITLE: MINI SAS 26P TO 26P	
					APPD BY		P/N: 1. AMS220010001	
					CUSTOMER P/N:			