



RJ45 8P8C Pinout

P1	P2
PIN1	1 CTS
PIN2	2 DSR
PIN3	3 RXD
PIN4	4 GND
PIN5	5 GND
PIN6	6 TXD
PIN7	7 DTR
PIN8	8 RTS

电气特性:

1. 100%开路、短路、断路测试。
2. 绝缘阻抗: 10M Ohm Min
3. 导通阻抗: 2 Ohm MAX
4. 耐压: DC 300V, 0.01/Sec



NO.	NAME	Description	QTY	Unit
6	胶料	45P PVC, 蓝色, MOLDED, ROHS	A/R	G
5	胶料	LDPE, MOLDED, ROHS	A/R	G
4	插头	USB TYPE AM 镀镍, ROHS	1	PCS
3	PCB	PCBA WITH FT232+ZT213 CHIP, ROHS	1	PCS
2	水晶头	RJ45 MALE, 8P8C, PIN G/F	1	PCS
1	线材	28AWG*8C, BARE COPPER, 蓝色 PVC JACKET, ROHS	A/R	M

A	INITIAL RELEASE	25/08/06													
REV	DESCRIPTION OF CHANGE	DATE													
<table border="1"> <thead> <tr> <th colspan="2">TOLERANCE</th> <th rowspan="4"> </th> <th rowspan="4">REV</th> <th rowspan="4">A</th> </tr> <tr> <th>INCHES</th> <th>M/M</th> </tr> </thead> <tbody> <tr> <td>.X</td> <td>.015 .30</td> </tr> <tr> <td>.XX</td> <td>.010 .10</td> </tr> <tr> <td>.XXX</td> <td>.005 .05</td> </tr> </tbody> </table>			TOLERANCE			REV	A	INCHES	M/M	.X	.015 .30	.XX	.010 .10	.XXX	.005 .05
TOLERANCE			REV	A											
INCHES	M/M														
.X	.015 .30														
.XX	.010 .10														
.XXX	.005 .05														
OIKWAN 东莞市嵩群实业有限公司 DONGGUAN AIQUN INDUSTRIAL CO., LTD.															
DRAWN BY	TONY CHAN	CUSTOMER:													
CHECK BY		DATE 25/08/06 DWG NO.:													
CUSTOMER. P/N:		P/N: ARJ160010001													
TITLE: USB TO RJ45 CABLE															