



PIN ASSIGNMENT:

MINISAS 4I(HOST)		SATA 7P(TARGET)	
P0		P4	
GND	A15	GND	7
TX4+	A16	RX4+	6
TX4-	A17	RX4-	5
GND	A18/B18	GND	4
RX4-	B17	TX4-	3
RX4+	B16	TX4+	2
GND	B15	GND	1
P3		P3	
GND	A12	GND	7
TX3+	A13	RX3+	6
TX3-	A14	RX3-	5
GND	A15/B15	GND	4
RX3-	B14	TX3-	3
RX3+	B13	TX3+	2
GND	B12	GND	1
P2		P2	
GND	A4	GND	7
TX2+	A5	RX2+	6
TX2-	A6	RX2-	5
GND	A7/B7	GND	4
RX2-	B6	TX2-	3
RX2+	B5	TX2+	2
GND	B4	GND	1
P1		P1	
GND	A1	GND	7
TX1+	A2	RX1+	6
TX1-	A3	RX1-	5
GND	A4/B4	GND	4
RX1-	B3	TX1-	3
RX1+	B2	TX1+	2
GND	B1	GND	1

正接点

- 电气特性:
- 1.100%开路、短路、断路测试。
 - 2.绝缘阻抗: 10M Ωhm Min
 - 3.导通阻抗: 2 Ωhm MAX
 - 4.耐压: DC 300V,0.01/Sec

防尘盖 ⑪



NO.	PART NAME	SPEC DESCRIPTION	QT'Y	UNIT
11	防尘盖	8087 防尘盖	1	pcs
10	标签	上光膜贴纸, 白底黑字, W6*L24, 印字内容: "P1&P2&P3&P4"	4	pcs
9	插头	SATA 7P 母头, 端子镀金: G/F, 黑色胶芯, 弹片式	4	pcs
8	编织网	黑色编织网 OD: 10mm, PET	A/R	mm
7	醋酸胶布	醋酸胶布 W=25±10mm	A/R	mm
6	胶料	45P PVC 黑色 ROHS	A/R	g
5	胶料	本色低密度PE料	A/R	g
4	胶料	PBT+30%GF 黑色 ROHS	A/R	g
3	弹片	不锈钢弹片, 10度高弹片	5	PCS
2	PCBA	MINISAS PCB, PIN: Au 15U", 100±10 ohm	1	PCS
1	线材	<30AWG*2C+2d>*AL+MYLAR, OD: 0.97*2.17MM, 100±5 ohm。	A/R	mm

A	INITIAL RELEASE	25/09/08
REV	DESCRIPTION OF CHANGE	DATE
TOLERANCE		
INCHES MM		
.X	.015	.30
.XX	.010	.10
.XXX	.005	.05
DRAWN BY	Wu Siyuan	
CHECK BY		
CUSTOMER P/N:	P/N: AMS1S0010001	

OIKWAN® 东莞市蔼群实业有限公司
DONGGUAN AIQUN INDUSTRIAL CO.,LTD.

SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	CUSTOMER:		
DATE	25/09/08	DWG NO:		
TITLE: MINISAS 8087-4*SATA				